

## **TRANSMISSION 80W/90 GL-5**

: 02.01.13

: 22.12.14

Date of Issue Revision Date

Revision : 01

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name and code	TRANSMISSION 80W/90 GL-5
Product use	Automotive Gear Oil
Producer/supplier	Reksoil Petrokimya San. Ve Tic. A.Ş
Address	Aydınlı Mh. Birlik Organize San. Böl. Doğu Cad. No: 19-21
	34953 Tuzla/İSTANBUL/ TÜRKİYE
	Tel: 0216 593 35 70 Fax: 0216 593 35 78

#### 2. COMPOSITION / INFORMATION ABOUT INGREDIENTS

A mixture of base oil and performance additives.

CAS NO. / EC NO.	Chemical Composition	% Rate	Symbol(s)	Risk Phrase(s)
Mixture	Base Oil	65-95	-	-
68649-42-3 /	Zinc	<=1.6	N, Xi	R51/53
272-028-3	alkyldithiophosphate	<u> </u>	14, 241	R36/38 R41
Proprietary	Methacrylate copolymer	<=0,1	Xi	R36



## **TRANSMISSION 80W/90 GL-5**

Date of Issue: 02.01.13Revision Date: 22.12.14	Revision : 01
3. HAZARDS IDENTIFICATION	
Physical / Chemical Hazards	Not classified as dangerous.
Human health hazards	Not classified as dangerous.
<b>Environmental Hazards</b>	Not likely to be harmful to aquatic organisms.
4. FIRST-AID MEASURES Eye contact	Hold the eyelids apart with clean hands and flush with running water for at least 15 minutes.
Skin contact	Rinse thoroughly with running water and soap. Take off contaminated clothes and should be washed contacted area on skin with water. You should see the doctor if irritate keeps continue on the skin.
Ingestion	DO NOT induce vomiting! Wash the mouth out with water. In case of nausea or any other symptoms seek medical assistance and show the label/container.
Inhalation	Remove the person to fresh air. If the person has breathing difficulties, seek medical assistance.

## **5. FIRE-FIGHTING MEASURES**

Suitable Extinguishers And Fire Fighting Method	Should be used foam, dry chemical and water spry at small-scale fires. Shoul call fire department at large fire.	
Unsuitable Extinguishers And Fire Fighting Method	Do not intervene fire with water.	
Special Situations After Combustion	Toxic gases consist After Combustion. May burn at high temperatures.	
Special protective equipment for Fire- fighting	Should be used protective clothing and oxygen mask for extinguishing Indoor locations fires by trained personnel.	



## **TRANSMISSION 80W/90 GL-5**

Date of Issue: 02.01.13Revision Date: 22.12.14	Revision : 01	
6. ACCIDENTAL RELEASE MEA	SURES	
Personal precautions	Use personal protective equipment from item 8. Stand upwind from the release site.	;
Environmental precautions	Avoid spilling into water, sewerage and drainage systems by digging a protective ditch and/or setting up partitions of dry sand, soil or similar absorbent material. Use floating dams for water spills.	
Methods for cleaning-up and recovery	Absorb the spilt product with absorbent or inert material. Store the waster material and contaminated surface layer of soil that was removed in closed containers in well-ventilated premises. Hand over for disposal to legal entities for hazardous waste disposal, authorized by the Ministry in charge of environmental protection.	l 3
Additional warnings	In case of larger spills, notify the communication unit at 112.	

#### 7. HANDLING AND STORAGE

#### Handling

Safety precautions	Use product in well ventilated premises. Keep away from sources of heat and ignition.	
Safe handling advice	Avoid contact with skin and eyes.	
Storage: Technical measures and storage	ge conditions	
Suitable	It is recommended that base oil be stored in covered or closed area. Recommended storage temperature is 5-40 °C.	
To be avoided	Do not expose to direct sunlight or higher temperatures, avoid contact wi water or strong oxidants.	
Packaging materials		
Recommended	Material resistant to hydrocarbons.	
Not suitable	Anything else.	



## **TRANSMISSION 80W/90 GL-5** Date of Issue : 02.01.13 : 01 **Revision Date** : 22.12.14 Revision 8. EXPOSURE CONTROLS / PERSONAL PROTECTION **Technical measures for reducing** Ensure good ventilation of premises. exposure See item 7. **Control parameters** Personal protective equipment During regular work respiratory protective equipment is not required. In special **Respiratory protection** cases (e.g. spills) use full face protective mask and in case of fire self-contained pressurized air breathing apparatus. Hand protection Gloves made of PVC or neoprene, resistant to oils, greases, alkali and acids. Eye protection Protective goggles with side protection or protective visor. Protective clothes and footwear. Skin and body protection Smoking, eating and drinking is prohibited during handling this product. Wash Special hygienic and safety precautions hands before each work break. **Additional warnings** Immediately remove contaminated clothes and footwear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physica	l properties				
State:	Liquid	Color:	Amber	Odor:	Petroleum odor



## **TRANSMISSION 80W/90 GL-5**

: 02.01.13

: 22.12.14

Date of Issue Revision Date

Revision : 01

### **Chemical properties**

Characteristics	Unit	Values	Method
Density @ 15 °C	g/cm <sup>3</sup>	0,87-0,91	ASTM D 4052
Flash Point	°C	Min. 220	ASTM D 92
Kinematic Viscosity@100 °C	mm <sup>2</sup> /s	14,5-18,5	ASTM D 445

## **10. STABILITY AND REACTIVITY**

Stability	Stabile at normal conditions.
Conditions to avoid	High temperature and direct sunlight.
Materials to avoid	Avoid contact with water and strong oxidants.
Hazardous decomposition products	Forming of dangerous products not expected at normal storage conditions.

#### **11. TOXICOLOGICAL INFORMATION**

Eye contact	If accidental eye contact can cause temporary blindness.
Skin contact	Prolonged or repeated contact can cause skin irritation. If skin contact with hot product that creates skin burns.
Ingestion	There is no any information.
Respiratory	Eye, nose and throat will be irritated if fog or mist breathes. Hot product vapor irritates the upper respiratory tract.



#### **TRANSMISSION 80W/90 GL-5**

Date of Issue Revision Date	: 02.01.13 : 22.12.14		Revision	: 01
12.	ECOLOGICAL			
Eco	toxicity	Does not harm the aquatic life forms. Spills mak prevent oxygen transfer.	e film layer on	water and
Mo	bility	Spilled product will cause pollution of groundwater.		
Per	sistence and degradability	Have the ability to accumulate in the soil.		

## **13. DISPOSAL CONSIDERATIONS**

According to current legislation should be eliminated by licensed personnel.

#### **14. TRANSPORT INFORMATION**

Transportation is not dangerous. Not classified as hazardous for transport.

## **15. REGULATORY INFORMATION**

- S2 Keep out of the reach of children
- **S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S29 Do not empty into drains.
- **S39** Wear eye/face protection.
- **S46** If swallowed, seek medical advice immediately and show this container or label



TRANSMISSION 80	DW/90 GL-5	
Date of Issue : 02.01. Revision Date : 22.12.		n : 01
<b>16. OTHE</b>	R INFORMATION	
Relevant R	Phrases	
R41	Risk of serious damage to eye.	
R38	Irritating to skin	
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environm	ient.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of this company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.