



Motor Oil & Lubricants

REXOIL

PLATINUM EXTRA

10W-40 CI-4/SL

Super High Performance (SHPD) Diesel Engine Oil

Full Synthetic

REXOIL PLATINUM EXTRA 10W-40 is high performance diesel engine oil which is prepared with synthetic base oils and advanced additive packages to provide excellent low temperature fluidity, high temperature viscosity retention, and volatility control. It is recommended for passenger cars and commercial vehicles, European and American design, low-emission, turbocharged engines. It is also recommended for vehicles that are working on roads and high speed / heavy load, light and heavy truck transport over short distances as well as upload / download operating, construction and agricultural land, such as vehicles running under heavy load conditions.

Properties

- Provides excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion.
- Contains intelligent molecules that cling to your engine and form an extra layer that protects from start up.
- Provides easily the first work at low temperatures by its excellent viscosity.
- Extends oil change intervals even at high sulfur fuel use.

Existing OEM Approvals

- Volvo VDS-3
- Renault VI RLD-2
- Mack EO-N

Approvals and Specifications

- API CI-4/CH-4/CG-4/CF-4/CF
- ACEA E5/E7-12 (2012)
- Renault VI RLD-2
- MB-Approval 228.3
- Volvo VDS-3
- MTU Oil Category 2
- Deutz DQC-III-05
- Detroit Diesel
- Caterpillar ECF-2
- API SL/SJ
- ACEA A3/B4-12 (2012)
- MAN M 3275
- Mack EO-M PLUS
- Mack EO-N
- JASO DH-1
- Global DHD-1
- CUMMINS CES 20076 / 20077/20078

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 145
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -35
Total Base Number, mg KOH/g	ASTM D2896	Min. 10,0