

## **REXOIL CHROME LPG**

## 20W-50 SL/CF

**REXOIL CHROME LPG 20W-50**, engine oil that can be use by confidence for four seasons especially heavily used gasoline and LPG. It has been formulated with high quality base oils and performance additives and it has been adapted perfectly catalysts and using unleaded petrol or LPG vehicles.

## Properties

- Excellent viscosity control feature allows the fuel economy.
- Makes the first work easy in the cold, makes effective lubrication at hot weather.
- Effective detergent and dispersant additives prevent deposit formation and keeps engine clean.

## Approvals and Specifications

- API SL/CF
- ACEA A3/B3-04

- VW 501.01 / 505.00
- MB Approval 229.1

**Technical Properties** 

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	16,3 – 21,9
Viscosity Index	ASTM D2270	Min. 110
Flash Point, °C	ASTM D92	Min. 230
Pour Point, °C	ASTM D97	Max24

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr