



Motor Oil & Lubricants

REXOIL

PREMIUM RACING

10W60 SN

REXOIL PREMIUM RACING 10W60 is full synthetic engine oil that has been formulated ultra-high performance synthetic base oils and new technology additive packages. **REXOIL PREMIUM RACING 10W60** can be used in the most difficult operating conditions (motorways, dense city traffic...), and is appropriated for all driving types, in particular for sporting or intense drive, and for every season.

Properties

- Protective lubricant film at extremely high operating temperatures.
- Offers extra reserve needed to resist extreme operating conditions during rallying and racing.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.
- Excellent protection against wear, corrosion and foam.
- Reduces oil volatility and therefore oil consumption and the need for top-up.

Approvals and Specifications

- API SN/SM/CF
- ACEA A3/B4-12 (2012)
- MB-Approval 226.5/229.3/229.5
- Opel GM-LL-B-025
- PSA Peugeot Citroën B71 2296
- Renault RN0710 / RN0700
- VW 502 00/505 00
- Porsche A40
- FORD WSS-M2C913-C
- FORD WSS-M2C913-D
- Opel GM-LL-A-025
- BMW Longlife - 01



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	21,9 – 26,1
Viscosity Index	ASTM D2270	Min. 165
HTHS Viscosity @ 150 °C, mPa.s	ASTM D4683	Min. 3,8
Cold Cranking Viscosity@ -25 °C, cP	ASTM D5293	Max. 6700
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -38
Total Base Number, mg KOH/g	ASTM D 2896	Min. 8,5