



Motor Oil & Lubricants

REXOIL HYDRO

REXOIL HYDRO is high quality hydraulic oils which formulated with quality base oils and oxidation, corrosion and rust inhibitors additives. It is recommended to use in many industrial and mobile hydraulic systems.

Properties

- Provides very good protection against corrosion, foaming and mud creation.
- Due to easily filterable properties, it can be safely used in hydraulic system.
- Resistant to high temperatures and oxidation.
- No damage to the sealing element.

Approvals and Specifications

- DIN 51524 Part 2
- Cincinnati Machine P-68, P-69, P-70
- Bosch Rexroth
- AFNOR NFE 48-690, NFE 48-691
- GM LS-2
- SAE MS1004
- ISO 11158 (HM)
- Denison HF-0, HF-1, HF-2
- U.S. Steel 127, U.S. Steel 136
- Eaton Vickers M-2950-S
- Eaton Vickers I-286-S
- GM LS-2
- JCMAS HK
- ASTM D6158-05(HM)



Motor Oil & Lubricants

Technical Specifications

| Test | Method | Typical Properties | | | | | |
|--------------------------------------|---------------|--------------------|-------------|-------------|-------------|-------------|----------|
| | | ISO GRADE | 22 | 32 | 37 | 46 | 68 |
| Kinematic Viscosity (40°C), [cSt] | ASTM D445 | 19.8 - 24.2 | 28.8 - 35.2 | 35.2 - 41.4 | 41.4 - 50.6 | 61.2 - 74.8 | 90 - 110 |
| Viscosity Index | ASTM D2270 | Min. 100 | Min. 100 | Min. 95 | Min. 95 | Min. 95 | Min. 90 |
| Flash Point, °C | ASTM D92 | Min.170 | Min. 205 | Min. 210 | Min. 215 | Min. 215 | Min. 220 |
| Pour Point, °C | ASTM D97 | Max. -25 | Max. -25 | Max. -25 | Max. -25 | Max. -25 | Max. -20 |