

### REXOIL

#### TITANIUM POWER SERIES

**REXOIL TITANIUM POWER SERIES**, high performance Synthetic Technology mono grade engine oils which is formulated with high-quality refined Synthetic base oils and advanced additives. **REXOIL TITANIUM POWER SERIES** are recommended for lubrication of engines and transmission under wide range of engine loads and conditions for all types of vehicles both off-highway & on-highway applications.

**Properties** Shows superior protection against oxidation, corrosion and foaming.

- Contains special detergents so that it is suitable for high temperature applications.
- Protects the engine against all kinds of rust and corrosion and extends the life.
- 

#### Approvals and Specifications

- API CF/SF

#### Technical Properties

Test	Method	Typical Properties				
SAE GRADE		10W	30	40	50	60
Kinematic Viscosity (100°C) [cSt]	ASTM D445	4,5 - 6,5	9,3 – 12,5	12,5 – 16,3	16,3 -21,9	21,9-26,1
Viscosity Index	ASTM D2270	Min. 100	Min. 95	Min. 95	Min. 95	Min. 105
Flash Point, °C	ASTM D92	Min. 185	Min. 220	Min. 230	Min. 235	Min. 240
Pour Point, °C	ASTM D97	Max. -27	Max. -18	Max. -15	Max. -15	Max. -15
Total Base Number, mgKOH/g	ASTM D 2896	Min. 7,0	Min. 7,0	Min. 7,0	Min. 7,0	Min. 7,0