

REXOIL COMPRESSOR OILS

REXOIL® COMPRESSOR OILS have been formulated from high quality base oils and additives to provide in a variety of rotary screw compressors, screw type compressors and reciprocating air compressors.

Properties

- Its excellent thermal and oxidation stability provide outstanding long oil life characteristics.
- It has thermal stability property at high temperature.
- It has high protection to rusting.
- They can help reduce compressor component wear and thereby reduce maintenance requirements.

Approvals and Specifications

- BS 489
- DIN 51515
- MIL-L-17672D
- U.S. Steel 120, U.S. Steel 125
- Brown Boveri HT GD 90 117E
- Siemens TLV901304
- General Electric GEK-32568F
- Solar Turbines ES 9-224

Technical Properties

Test	Method	Typical Values				
		ISO GRADE	32	46	68	100
Kinematic Viscosity (40°C) [cSt]	ASTM D445		28,8 – 35,2	41,4 – 50,6	61,2 – 74,8	90 - 110
Viscosity Index	ASTM D2270		Min. 95	Min. 95	Min. 95	Min. 95
Flash Point, °C	ASTM D92		Min. 210	Min. 220	Min. 225	Min. 230
Pour Point, °C	ASTM D97		Max. -25	Max. -25	Max. -25	Max. -20