



Motor Oil & Lubricants

REXOIL

ATF DEXRON III

REXOIL ATF DEXRON III is formulated with high quality base oils and special additives to ensure the proper operation of the automatic transmission where Dexron® (II or III) or Mercon performance is required. It's also suitable as Power Steering Fluid. Suitable for use in transmissions of trucks, buses and public works machineries when a fluid type ALLISON C4 is required.

Properties

- Very high viscosity index linked with excellent viscosity stability in operation.
- Enhanced high temperature performance giving improved and more durable shift feel on gear changes.
- Enhanced life of copper alloy based components and improved fluid service.
- Enhanced friction durability prolongs transmission life and promotes smooth shifting.

Approvals and Specifications

- General Motors Dexron IIIH
- GM Type A Suffix A
- MB-Approval 236.1, 236.5
- Voith H55.6335
- ZF TE-ML-02F, 03D, 04D, 09, 11B, 14A, 17C
- General Motors Dexron IIIM
- Ford MERCON®
- Allison C-4
- MAN 339 TYP Z1, V1
- CAT TO-2

Technical Properties

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	6,4 – 8,9
Viscosity Index	ASTM D2270	Min. 165
Flash Point, °C	ASTM D92	Min. 195
Pour Point, °C	ASTM D97	Max. -45