

REXOIL DIAMOND PRO RX

5W/30 SN/CF

(Low SAPS)

REXOIL DIAMOND PRO RX 5W/30 is full synthetic engine oil for new generation engines which is developed with high performance additives and synthetic base oils. It is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's).

Properties

- It has a low sulfur and phosphorus content.
- Provides high resistance to tear due to high viscosity index.
- Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additives.
- Helps to reduce particulate build up in Diesel Particulate Filters.
- Helps to reduce poisoning of Gasoline Catalytic Converters.
- Satisfies the most demanding manufacturer service plans by permitting extra-long oil change intervals.
- Provides superior performance under extreme cold start up conditions.

Existing OEM Approvals

Renault RN0720

Approvals and Specifications

- API SN / API SM / API SL
- ACEA C1-08 / C4-10
- Renault RN0720
- Ford WSS-M2C913-C
- JASO DL-1

- API CF
- MB-Approval 229.51
- MB-Approval 226.51
- Ford WSS-M2C934-B
- ACEA A5/B5-08

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr



Technical Specifications

8

0	Test	Method	Typical Properties
Kir	nematic Viscosity (100°C), [cSt]	ASTM D445	9,3 - 12,5
	Viscosity Index	ASTM D2270	Min. 160
	Flash Point, °C	ASTM D92	Min. 200
115	Pour Point, °C	ASTM D97	Max38
Total Base Number, mg KOH/g		ASTM D 2896	Min. 7,5

0

0

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş. Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – İSTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr