

PLATINUM LS 10W40 CI-4

: 02.01.13

Date of Issue Revision Date

Revision : 01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDERTAKING

| Product name and code | PLATINUM LS 10W40 CI-4 |
|-----------------------|---|
| Product use | Multigrade Engine Oil |
| Producer/supplier | Reksoil Petrokimya San. Ve Tic. A.Ş |
| Address | Aydınlı Mh. Birlik Organize San. Böl. Doğu Cad. No: 19-21 |
| | 34953 Tuzla/İSTANBUL/ TÜRKİYE |
| | Tel: 0216 593 35 70 Fax: 0216 593 35 78 |

2. COMPOSITION / INFORMATION ABOUT INGREDIENTS

A mixture of base oil and performance additives.

| CAS NO. / EC NO. | Chemical Composition | % Rate | Symbol(s) | Risk Phrase(s) |
|---------------------|---------------------------|----------|-----------|----------------|
| Mixture | Base Oil | 65-95 | - | - |
| 68649-42-3 / | Zinc | <=1.6 | N, Xi | R51/53 |
| 272-028-3 | alkyldithiophosphate | <u> </u> | 14, 241 | R36/38 R41 |
| Proprietary | Methacrylate copolymer | <=0,1 | Xi | R36 |



PLATINUM LS 10W40 CI-4

| Date of Issue : 02.01.13 Revision Date : 22.12.14 | Revision : 01 |
|--|---|
| 3. HAZARDS IDENTIFICATION | |
| Physical / Chemical Hazards | Not classified as dangerous. |
| Human health hazards | Not classified as dangerous. |
| Environmental Hazards | Not likely to be harmful to aquatic organisms. |
| 4. FIRST-AID MEASURES Eye contact | Hold the eyelids apart with clean hands and flush with running water for at least 15 minutes. |
| Skin contact | Rinse thoroughly with running water and soap. Take off contaminated clothes and should be washed contacted area on skin with water. You should see the doctor if irritate keeps continue on the skin. |
| Ingestion | DO NOT induce vomiting! Wash the mouth out with water. In case of nausea or any other symptoms seek medical assistance and show the label/container. |
| Inhalation | Remove the person to fresh air. If the person has breathing difficulties, seek medical assistance. |

5. FIRE-FIGHTING MEASURES

| Suitable Extinguishers And Fire Fighting Method | Should be used foam, dry chemical and water spry at small-scale fires. Should call fire department at large fire. |
|--|---|
| Unsuitable Extinguishers And Fire Fighting Method | Do not intervene fire with water. |
| Special Situations After Combustion | Toxic gases consist After Combustion. May burn at high temperatures. |
| Special protective equipment for Fire- fighting | Should be used protective clothing and oxygen mask for extinguishing Indoor locations fires by trained personnel. |



| PLATINUM LS 10W40 CI-4 | | | |
|--|---|-------------------------------------|--------------------------------|
| Date of Issue: 02.01.13Revision Date: 22.12.14 | | Revision | : 01 |
| 6. ACCIDENTAL RELEASE MEAS | SURES | | |
| Personal precautions | Use personal protective equipment from item 8. Sta site. | nd upwind fron | n the release |
| Environmental precautions | Avoid spilling into water, sewerage and drainag protective ditch and/or setting up partitions of dry sa material. Use floating dams for water spills. | | |
| Methods for cleaning-up and recovery | Absorb the spilt product with absorbent or inert material and contaminated surface layer of soil th containers in well-ventilated premises. Hand over the for hazardous waste disposal, authorized by the environmental protection. | hat was remove for disposal to l | ed in closed legal entities |
| Additional warnings | In case of larger spills, notify the communication un | it at 112. | |
| 7. HANDLING AND STORAGE | | | |
| Handling | | | |
| Safety precautions | Use product in well ventilated premises. Keep awa ignition. | y from sources | of heat and |
| Safe handling advice | Avoid contact with skin and eyes. | | |
| Storage: Technical measures and storage conditions | | | |

SuitableIt is recommended that base oil be stored in covered or closed area.
Recommended storage temperature is 5-40 °C.To be avoidedDo not expose to direct sunlight or higher temperatures, avoid contact with
water or strong oxidants.Packaging materialsMaterial resistant to hydrocarbons.Not suitableAnything else.



| PLATI | NUM | LS 10\ | N40 | CI-4 |
|-------|-----|--------|-----|----------|
| | | | | U |

| Date of Issue: 02.01.13Revision Date: 22.12.14 | | Revision | : 01 |
|--|---|--------------------------------------|---------------|
| 8. EXPOSURE CO | ONTROLS / PERSONAL PROTECTION | | |
| Technical measures f exposure | for reducing Ensure good ventilation of premis | jes. | |
| Control parameters | See item 7. | | |
| Personal protective e | equipment | | |
| Respiratory protection | on During regular work respiratory p cases (e.g. spills) use full face pro pressurized air breathing apparatu | ptective mask and in case of fire | - |
| Hand protection | Gloves made of PVC or neoprene | , resistant to oils, greases, alkali | and acids. |
| Eye protection | Protective goggles with side prote | ection or protective visor. | |
| Skin and body protec | ction Protective clothes and footwear. | | |
| Special hygienic and precautions | safetySmoking, eating and drinking is hands before each work break. | prohibited during handling this p | product. Wash |
| Additional warnings | Immediately remove contaminate | d clothes and footwear. | |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physica | l properties | | | | |
|---------|--------------|--------|-------|-------|----------------|
| State: | Liquid | Color: | Amber | Odor: | Petroleum odor |



PLATINUM LS 10W40 CI-4

Date of Issue Revision Date

Revision : 01

Chemical properties

: 02.01.13

: 22.12.14

| Characteristics | Unit | Values | Method |
|----------------------------|--------------------|--------------|-------------|
| Density @ 15 °C | g/cm ³ | 0,87-0,89 | ASTM D 4052 |
| Flash Point | °C | Min. 200 | ASTM D 92 |
| Kinematic Viscosity@100 °C | mm ² /s | 12,5-16,3 | ASTM D 445 |
| | |) <u>)</u> - | |

10. STABILITY AND REACTIVITY

| Stability | Stabile at normal conditions. |
|----------------------------------|--|
| Conditions to avoid | High temperature and direct sunlight. |
| Materials to avoid | Avoid contact with water and strong oxidants. |
| Hazardous decomposition products | Forming of dangerous products not expected at normal storage conditions. |

11. TOXICOLOGICAL INFORMATION

| Eye contact | If accidental eye contact can cause temporary blindness. |
|--------------|--|
| Skin contact | Prolonged or repeated contact can cause skin irritation. If skin contact with hot product that creates skin burns. |
| Ingestion | There is no any information. |
| Respiratory | Eye, nose and throat will be irritated if fog or mist breathes. Hot product vapor irritates the upper respiratory tract. |



| PLATINUM LS 10W40 CI-4 | |
|--|--|
| Date of Issue : 02.01.13 Revision Date : 22.12.14 | Revision : 01 |
| 12. ECOLOGICAL | |
| Ecotoxicity | Does not harm the aquatic life forms. Spills make film layer on water and prevent oxygen transfer. |
| Mobility | Spilled product will cause pollution of groundwater. |
| Persistence and degradability | Have the ability to accumulate in the soil. |

13. DISPOSAL CONSIDERATIONS

According to current legislation should be eliminated by licensed personnel.

14. TRANSPORT INFORMATION

Transportation is not dangerous. Not classified as hazardous for transport.

15. REGULATORY INFORMATION

- S2 Keep out of the reach of children
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S29 Do not empty into drains.
- **S39** Wear eye/face protection.
- S46 If swallowed, seek medical advice immediately and show this container or label



| PLATINUM LS 10W40 CI-4 | | | | |
|--------------------------------|--------------------------|---|------------|------|
| Date of Issue Revision Date | : 02.01.13 : 22.12.14 | | Revision | : 01 |
| 16. OTHER INFORMATION | | | | |
| Relevant R Phrases | | | | |
| | | | | |
| R | 841 | Risk of serious damage to eye. | | |
| R | 38 | Irritating to skin | | |
| R | 251/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic en | vironment. | |
| | | | | |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of this company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.