

New Generation Engine Oils Efficient Operation, Real Protection





INDUSTRIAL LUBRICANTS CATALOGUE



"The Right and the best product, " Aktas group which set out with this idea. As a result of long term research and development, REXOIL brand met with customers. REXOIL brand products; high quality base oils and high tech additives.

REXOIL aims to strong cooperation with manufacturer in all sectors thanks to industrial oils which are developed by REXOIL.

Today, REXOIL, automotive, machinery, marine, iron and steel, have a say in many industries such as ceramics developed on behalf of the special sequences. Increase the efficiency and stability of these products are developed to provide enterprises. At the same time REXOIL, sales and aftersales technical support processes are always next to the industrialists. Production losses due to failure to follow the correct process to minimise businesses.

REXOIL the power of the wide range of products from production, professional staff, excellent technical infrastructure and better with each passing day, and aims to become an expanding investments in industrial activities in this direction is at every point.





HYDRAULIC SYSTEM OILS



REXOIL HYDRO SUPER 32 / 46 / 68 / 100

It is a high viscosity index lubricating oil for hydraulic systems, formulated with high quality base oils and universal anti-wear additives. It provides superior protection thanks to the additives it contains to prevent foaming, oxidation, rust and corrosion.

CERTIFICATES AND STANDARDS

Denison Parker HF-0, HF-1, HF-2, Eaton Vickers M-2950-S, Eaton Vickers I-286-S3, Cincinnati Lamb P-68, P-69, and P-70, DIN 51524 (Part II, III) (2006), ANSI/AGMA 9005-E02-RO, ASTM D 6158 (HM, HV), ISO 11158 (HM, HV), GM LS-2, JCMAS P041 (HK), AIST 126, 127, Bosch RE 90 220, SAE MS 1004 (HM, HV) meets the requirements of.

REXOIL HYDRO 32 / 46 / 68 / 100

It is a high viscosity index lubricating oil for hydraulic systems, formulated with high quality base oils and universal anti-wear additives. It provides superior protection thanks to the additives it contains to prevent foaming, oxidation, rust and corrosion.

CERTIFICATES AND STANDARDS

REX

Denison Parker HF-0, HF-1, HF-2, Eaton Vickers M-2950-S, Eaton Vickers I-286-S3, Cincinnati Lamb P-68, P-69, and P-70, DIN 51524 (Part II, III) (2006), ANSI/AGMA 9005-E02-RO, ASTM D 6158 (HM, HV), ISO 11158 (HM, HV), GM LS-2, JCMAS P041 (HK), AIST 126, 127, Bosch RE 90 220, SAE MS 1004 (HM, HV) meets the requirements of.

REX



INDUSTRIAL GEAR OILS

REXOIL GEAR BOXES

68 / 100 / 150 / 220 / 320 / 460 / 680

It is a lubricating oil for extreme pressure (EP) gearboxes. It has been formulated with mineral base oils and additive packs. It has been specially developed for gearboxes working under a heavy load. It is recommended for all kinds of covered industrial gearboxes.

CERTIFICATES AND STANDARDS

AISE 224, David Brown S1.53.101(E), AGMA 9005-E02 and strong FAG FE-8 performance meets the requirements of.



New Generation Engine Oils Efficient Operation, Maximum Protection



RE REXOIL IL

SLIDEWAY OILS

REXOIL SLIDE OIL 32 / 68 / 220 Slide Oil

It is an oil for workbench slides, formulated with EP additives, high quality base oils, and adhesion-reinforcing special additives. It is recommended for horizontal and vertical slides of all kinds of workbenches.

HEAT TRANSFER OILS



HEAT TRANSFER OIL 32 / 46 Industrial Process Heat Transfer Oil

REX OIL

REX OIL

It has been formulated with well refined paraffin base oils. Its thermal stability and resistance to oxidation is excellent. It never has a corrosive effect on steel or copper. It can be safely used in closed systems at a working temperature up to 315°C and in open systems up to 200°C.

PROCESSING OILS

REXOIL SHINE PARAFFINIC PROCESS SERIES⁹ 32 / 46 / 68 / 100 / 150 / 220 / 320 / /460

It is a paraffin-based, high viscosity index general purpose mineral oil lubricant. It is recommended for permanently installed diesel, gas or twin-fuel engines, air compressors, power chainsaws, pit saws, and circulation systems. It can be also used as a heat transfer fluid for electric motors, air cleaners, bearings, machine parts and chains.



0

MONOGRADE SERIES

REXOIL TITANIUM POWER SERIES 10-30-40-50W



It is a single degree, general purpose, mineral-based lubricant formulated with paraffin base oils and additive packages. It is recommended for high rotation and high power engines of heavy duty machines and heavy duty vehicles.

APPROVALS AND STANDARDS

API CF/SF meets the requirements.

REXOIL TITANIUM SERIES 10-30-40-50-60W



It is a single degree, general purpose, mineral-based lubricant formulated with paraffin base oils and additive packages. It is recommended for diesel and gasoline engines working under light or medium conditions.

APPROVALS AND STANDARDS API CC/SC meets the requirements.

MARINE ENGINE OILS

REXOIL ALESTA 5070

Lubricant for cylinders of low rpm diesel engines

It is a lubricant developed for the cylinders of ship engines running on heavy fuel containing sulfur up to 4%. It has been formulated with well-refined base oils and additive packages.

REXOIL ALESTA M 4040

Medium rpm Diesel Engine Lubricant

This lubricant has been formulated for medium rpm diesel engines used for heavy duty and running on heavy fuel having a high sulfur content. It is recommended for engines and power plants below age 10 and running on fuel whose sulfur content is above 3%.

REXOIL ALESTA S SERIES 3012 / 4012

Medium and High rpm Diesel Engine Lubricant

It is a diesel engine lubricant for medium and high rpm diesel engines running on fuel having a sulfur content up to 1%. It is also recommended for low lubricant volume and high rpm diesel engines used for heavy duty in fishing boats.

REXOIL ALESTA R SERIES 3030 / 4030

Medium rpm Diesel Engine Lubricant

ALESTA R SERIES is high TBN value diesel engine lubricant formulated with special additive packages and high quality base oils for medium rpm crank piston type of ship engines and supplementary engines running on heavy fuel having a sulfur content below 3%. It is recommended for all kinds of ship diesel engines for whose gear transmission systems SAE 30 and SAE 40 lubricants are recommended.

REX REXOIL EXOIL



minuBaok

GREASES



<mark>REXOIL NEO</mark> High Perforn Water Resist				XOIL
NIGINO	0	1	2	3

NLGI No	0	1	2	3
Color	Green	Green	Green	Green
Type of soap	Calcium	Calcium	Calcium	Calcium

It is a water resistant multi-purpose calcium grease containing fibers, formulated with good quality base oils and high performance additives. It is recommended for medium or high rpm engines equipped with flat or ball bearings where working temperature is

·lt adheres on metal in humid or wet environments to provide excellent resistance to washing away with water.

·It provides efficient protection from wear and corrosion

Iubricated



It is an automotive grease formulated with high quality mineral base oils, specially selected additives, and another additive for extreme pressures. It is recommended for industrial applications under heavy duty and impact conditions, and for wheel bearings and central lubrication systems of automobiles, commercial vehicles, sports utility vehicles, agricultural machines, and heavy duty machines.

·It prevents rust and corrosion to extend the system's service life.

·It is resistant to water and oxidation, and can be easily pumped.

·It prevents wearing at impact and vibrating loads.

·lt provides additional protection from rinsing with water.



NLGI No	1	2	3
Color	Red	Red	Red
Type of soap	Calcium	Calcium	Calcium

It is a water resistant, calcium soap general purpose grease formulated with high quality base oils and superior additives. It is recommended for medium and high rpm ball bearings, low rpm flat bearings and chasses used for light duty purposes at low working temperatures.

It is resistant to water and protects the system from wear and corrosion.

It prevents foreign objects from entering the system and ensures the system to be used in economical way.

It increases the system's performance by ensuring fast and efficient lubrication at low working temperatures.

REXOIL NEON GREASE Extra Perform Lithium Soap			
NLGI No	1	2	3
Color	Light brown	Light brown	Light brown
Type of soap	Lithium	Lithium	Lithium

It is lithium soap grease formulated with superior quality base oils and additives, used for a wide range of purposes in various industries. It is recommended for the wheel ball bearings and central lubrication systems of automobiles, commercial vehicles, sports utility vehicles, agricultural machines and heavy duty machines not used at extremely heavy loads or extremely high temperatures. It can also be safely used in ball bearings of electric motors.

It prevents rust and corrosion to extend the system's service life.

·It is resistant to water and oxidation, and can be easily pumped.

·lt prevents wearing at impact and vibrating loads.

·It provides additional protection from rinsing with water.



New Generation Engine Oils Efficient Operation, Maximum Protection





AK AKTAS GROUP

THE



or u P

O AKTAS

7 7 7 7 7 7

11

New Generation Engine Oils Efficient Operation, Real Protection



Reksoil Petrokimya San. ve Tic. A.Ş.

FACTORY: Birlik Organize San. Bölg. Doğu Cd. No:21 Tuzla - Istanbul / TURKEY Tel: +90 216 593 35 70 (Pbx) Fax: +90 216 593 35 78 www.rexoil.com.tr BRANCH: İçerenköy Mh. Erkut Sk. Üner Plaza No: 12/15 PK 34752 Ataşehir - Istanbul / TURKEY Tel: +90 216 577 43 00 (Pbx) Fax: +90 216 577 43 08