

# REXOIL

## WHITE OIL

**REXOIL WHITE OIL** group are paraffinic, clear, colorless and odorless white process oils. Do not left under daylight and stored at room temperature.

### Area of Use

Plastic, rubber, chemical, agriculture, paper, textile industry, in particular skin oil, wax, ink and paint manufacturing, foam cutting, and also are used as raw materials in industrial lubricants.

### Technical Properties

Test	Method	Typical Properties				
		S-15	S-25	S-30	S-68	S-96
Kinematic Viscosity (40°C) [cSt]	ASTM D445	13,5-16,5	22,5 - 27,5	26,8 - 33,2	61,2 – 74,8	90 - 110
Kinematic Viscosity (100°C) [cSt]	ASTM D445	3,0 - 4,5	4,0 – 5,4	4,6 - 6,8	8,2 – 9,8	10,5 – 11,8
Viscosity Index	ASTM D2270	Min. 105	min. 105	Min. 105	Min. 105	Min. 100
Flash Point, °C	ASTM D92	Min. 160	Min. 205	Min. 210	Min. 220	Min. 235
Pour Point, °C	ASTM D97	Max. -12	Max. -12	Max. -12	Max. -10	Max. -10
Color (ASTM)	ASTM D1500	L0,5	L0,5	L0,5	L0,5	L0,5
Color (Saybolt)	ASTM D156	+30	+30	+30	+30	+30
<b>Carbon Distribution</b>						
% Aromatic	ASTM D3238	0,0	0,0	0,0	0,0	0,0
% Naphanic	ASTM D3238	31,7	31,8	32,2	32,2	32,5
% Paraffinic	ASTM D3238	68,3	68,2	67,8	67,8	67,5